

# FILLISTER HEAD SCREWS - MACHINE SCREWS



## MS24694C STAINLESS STEEL MACHINE SCREWS

Same style screws as MS24694, except stainless steel. Phillips head. (Formerly AN509C) Minimum tensile strength for stainless steel is 85,000 PSI.

HA

MS Part No.	AN509C No.	Thread Size	Length Inches	Price Each
MS24694C1	-8R4	8-32	9/32	---
MS24694C2	-8R5	8-32	11/32	---
MS24694C3	-8R6	8-32	13/32	---
MS24694C4	-8R7	8-32	15/32	---
MS24694C5	-8R8	8-32	17/32	---
MS24694C6	-8R9	8-32	19/32	---
MS24694C7	-8R10	8-32	21/32	---
MS24694C8	-8R11	8-32	23/32	---
MS24694C9	-8R12	8-32	25/32	---
MS24694C10	-8R13	8-32	27/32	---
MS24694C11	-8R14	8-32	29/32	---
MS24694C13	-8R16	8-32	1-1/32	---
MS24694C14	-8R17	8-32	1-3/32	---
MS24694C15	-8R18	8-32	1-5/32	---
MS24694C46	-10R4	10-32	9/32	---
MS24694C47	-10R5	10-32	11/32	---

MS Part No.	AN509C No.	Thread Size	Length Inches	Price Each
MS24694C48	-10R6	10-32	13/32	---
MS24694C49	-10R7	10-32	15/32	---
MS24694C50	-10R8	10-32	17/32	---
MS24694C51	-10R9	10-32	19/32	---
MS24694C52	-10R10	10-32	21/32	---
MS24694C53	-10R11	10-32	23/32	---
MS24694C54	-10R12	10-32	25/32	---
MS24694C55	-10R13	10-32	27/32	---
MS24694C56	-10R14	10-32	29/32	---
MS24694C57	-10R15	10-32	31/32	---
MS24694C58	-10R16	10-32	1-1/32	---
MS24694C59	-10R17	10-32	1-3/32	---
MS24694C60	-10R18	10-32	1-5/32	---
MS24694C61	-10R19	10-32	1-7/32	---
MS24694C62	-10R20	10-32	1-9/32	---
MS24694C92		1/4-28	3/8	---

## NAS387 SERIES MACHINE SCREWS



Type: NAS387 Material: Carbon Steel Type 1016 - 1024 Finish: Nickel Plate

Thread	Length	Part No.	Price
6-32	3/8	NAS387-632-6P	---
	7/16	NAS387-632-7P	---
	1/2	NAS387-632-8P	---
	5/8	NAS387-632-10P	---
	3/4	NAS387-632-12P	---
8-32	1/2	NAS387-832-8P	---
	5/8	NAS387-832-10P	---
	3/4	NAS387-832-12P	---
	7/8	NAS387-832-14P	---
10-32	1/2	NAS387-1032-8P	---
	5/8	NAS387-1032-10P	---
	3/4	NAS387-1032-12P	---
	7/8	NAS387-1032-14P	---
	1	NAS387-1032-16P	---
	1-1/8	NAS387-1032-18P	---
	1-1/4	NAS387-1032-20P	---
1/12	NAS387-1032-24P	---	

## AN502, AN503 FILLISTER HEAD SCREWS



AN502 (fine thread) and AN503 (coarse thread) drilled head, slotted fillister head screws are fabricated from steel meeting specification MIL-S-6050. Tensile strength 125,000 PSI. Cadmium plated, Type I, Class 3.

AN502			
AN502 Dash No.*	Length (In.)	Thread Size	Price Each
-10 -5	19/64	10-32	---
-10 -6	3/8	10-32	---
-10 -8	1/2	10-32	---
-10 -10	5/8	10-32	---
-10 -12	3/4	10-32	---
-10 -16	1	10-32	---
-416 -12	3/4	1/4-28	---
-416 -16	1	1/4-28	---

AN503							
AN503 Dash No.*	Length (In.)	Thread Size	Price Each	AN503 Dash No.*	Length (In.)	Thread Size	Price Each
-6 -4	1/4	6-32	---	-10 -6	3/8	10-24	---
-6 -6	3/8	6-32	---	-10 -8	1/2	10-24	---
-8 -4	1/4	8-32	---	-10 -10	5/8	10-24	---
-8 -6	3/8	8-32	---	-10 -12	3/4	10-24	---
-8 -8	1/2	8-32	---	-10 -16	1	10-24	---
-8 -10	5/8	8-32	---	-10 -24	1-1/2	10-24	---
-8 -16	1	8-32	---	-416 -8	1/2	1/4-20	---
				-416 -10	5/8	1/4-20	---
				-416 -12	3/4	1/4-20	---