CHERRY AEROSPACE RIVETS - SELF-PLUGGING CHERRY RIVETS

100° COUNTERSUNK (CR9162)



The self-plugging Cherry Blind Rivet is a 2-piece assembly - a hollow rivet and an inner member or stem, drawn into or through the hollow rivet. Cherry CR162 & CR163 series rivets are now replaced by CR9162 & CR9163 series rivets which are less expensive but does require the use of a rivet gun that comes with the req. nosepiece.

3/32" rivets and has a 728A9-104 nosepiece stored in the handle for installing 1/8" rivets......P/N 12-00701

Part No.	Head	Nominal	Grip	Price		
Part No.	Style	Dia.	Range	Each	100	1000
CR9162-4-2	Csk	1/8"	.063125			
CR9162-4-4			.188250			
CR9162-4-6			.313375			
CR9162-4-8			.438500			
CR9163-4-2	Univ.	1/8"	.063125			
CR9163-4-4			.188250			
CR9163-4-6			.313375			

UNIVERSAL HEAD (CR 9163)

CHERRY N RIVETS

Break mandrel rivets Conform to MIL-R-24243 & IFI-114 Standards



LOW COST


Substantial savings in installed costs can be realized when Cherry N Rivets are substituted for spotwelds, screws or bolts.

Quick and easy to use with hand or power riveters, Cherry N Rivets have endless fastening applications in manufacturing, maintenance.

Unusual mandrel design of Cherry N Rivets holds rivet and mandrel firmly together prior to installation and insures positive mandrel retention in the installed rivet.

NO MANDREL POP OUTS-

As the mandrel is drawn into the rivet, the end of the rivet sleeve closes in an elliptical configuration... locking the mandrel firmly in place!



PROTRUDING HEAD CHERRY N RIVET IDENTIFICATION CODE

First letter is rivet material:

A = 5052 Aluminum B = 5056 Aluminum C = Stainless M = Monel S= Steel U = Copper Second letter is mandrel material:

A = 7178 Aluminum C = Stainless S = SteelThird letter is head style:

P = Protruding L = Large

C = FlushFirst number is rivet diameter in 32nds of an inch:

For example,—4 is 4/32nds or 1/8" diameter

Second number is rivet maximum grip length in 16ths of an inch: For example,—6 is 6/16ths or 3/8" grip length

MINIMUM RIVET SHEAR AND TENSILE STRENGTH (IBS.) **CHERRY N RIVETS**

0.1=1.11.11.11.1							
Rivet Dia.	Steel Mand.		MS Series Monel Rivet Steel Mand.		CC Series Stainless Rivet Stainless		
Mand.			Grade 40		Grade 51		
	Shear	Tens	Shear	Tens	Shear	Tens	
3/32	125	175	200	300	230	280	
1/8	200	325	350	525	450	600	
5/32	325	450	600	900	750	1000	
3/16	430	650	750	1100	1000	1300	
1/4	750	1050	1450	2150	1700	2250	

CHERRY Q RIVETS

.063-.125

Structural—Self-plugging rivets

5/32"




HIGH SHEAR STRENGTH

CR9163-5-2 Univ.

Cherry Q Rivet mandrel plugs the entire length of the rivet sleeve, providing full shear strength values for structural or load-bearing applications.

Specially designed mandrel of the Q Rivet is engineered to effect a seal, upon installation which offers resistance to leakage.

VIBRATION RESISTANT





C = Stainless

C = Flush

Rivet sleeve curls over end of mandrel to insure its positive retention.

FLUSH HEAD PROTRUDING HEAD CHERRY Q RIVET IDENTIFICATION CODE

First letter is rivet material:

B = 5056 Aluminum A = 5052 Aluminum C = Stainless M = Monel S= Steel

Second letter is mandrel material: A = 7178 Aluminum S = Steel

Third letter is head style: L = Large

Fourth letter is type of rivet:

P = Protruding

Q = Cherry Q Rivet, structural, self-plugging

First number is rivet diameter in 32nds of an inch:

For example,—6 is 6/32nds or 3/16" diameter

Second number is rivet maximum grip length in 1/16 of an inch: For example,—8 is 8/16ths or 1/2" grip length

MINIMUM RIVET SHEAR AND TENSILE STRENGTH (IBS.) **CHERRY Q RIVETS**

Rivet Dia.	BS Series Alum Rivet Steel Mand.		MS S Monel Steel	Rivet	CC Series Stainless Rivet Stainless Grade 51			
Mand.	Grad	le 19	Grade 40					
	Shear	Tens	Shear	Tens	Shear	Tens		
5/32	525	450	950	900	1050	1000		
3/16	750	650	1450	1100	1650	1300		
1/4	1250	1050	2350	2150	2450	2250		

NOTE: SUBJECT TO PRICE AND AVAILABILITY OF CHERRY BRAND RIVETS. EQUIVALANT RIVETS MAY BE FURNISHED.