## CLO POLISHING PRODUCTS - DE-IC

#### CYCLO ORBITAL POLISHER MODEL #5

Note: Polishing pads are not included, but are required for use. See "Accessories" tab for available pads.

Precision machined and hand assembled for a lifetime of trouble-free operation, the Cyclo Polisher's dual heads orbit in a random, overlapping motion that mimics fine hand polishing. Leaves a dazzling, swirl-free shine every time.

The Cyclo Dual Head Orbital Polisher is the most effective means of polishing available today. Even in the hands of a novice, it is safe to operate and provides professional results every time. The difference lies in the tool's overall balance and its patented dual heads. The dual heads operate in a synchronized motion, providing the most effective results without fear of heat buildup; damage to trim pieces, moldings and gaskets; swirl marks, holograms and more. The low-vibration and balanced design allow for a more even application and better control when operating.

- Power Supply: 115 Volts, 60 Hertz, 220 Watts
- Motor: alternating current, semi-enclosed 24-bar commutator
- Speed: 3000 orbits/minute
- Output: 1/3 H.P. (.25 Kw)
  Weight: 6.5 lb. (2.9 kg)
- Head Rotation/Diameter: clockwise /4" · Electric Cord: 10' length, 16 ga/3SJTOW
- Housing: heavy-duty cast aluminum
- Polisher Only......P/N 09-35715

#### CYCLO POLISHER BONNETS

#### **GREEN POLISHING PADS**

· Sealant · Paint Polish · Paint Cleaner · Metal Sealant

With Velcro ......P/N 09-35732

Note: Polishing Pads with Velcro require the RUBBER PAD HOLDERS P/N 09-05524 listed with the Cyclo accessories



# CYCLO PROGUARD

ORBITAL BACKING PLATE
The Cyclo Toolmakers ProGuard Orbital Backing
Plate features permanently adhered high quality dense hook material (the same material that's used on the Rubber Pad Holders). This provides a much better mating hook and much more area of hook material. The color of the plate is white so you can

tell it is the new and improved version. Low profile for improved control and a non-marking bumper for safe operation. The advanced design still allows for faster pad centering, and is perfect for quick and easy pad 

#### CYCLO BRUSHES

AQUA SOFT CARPET BRUSH - • Fine Carpets • Durable Carpets Tile & Grout • Durable Carpets ......P/N 09-35742
 BLACK STIFF SCRUB BRUSH - • Tile & Grout • Truck Bed Liners. P/N 09-35740

#### CYCLO POLISHER ACCESSORIES

Proguard Orbital Backing Plate.....P/N 09-05524 



#### JET STREAM PBS BOOT SEALANT

PBS Prep is formulated for use before each PBS Boot Sealant application to avoid dulling and hard to remove build-up. PBS Prep will effectively clean pneumatic de-ice boots of all old treatments assuring the best results possible when applying PBS Boot Sealant. Failure to prepare de-ice boots with PBS Prep may result in dulling due to build-up. 32 ounces.

PBS	Prep	P/N	09-41711
PBS	Sealant	P/N	09-41712

### GOODRICH DE-ICER CONDUCTIVE CEMENT **EDGE SEALING COMPOUND**

The Goodrich De-Icer Systems are formulated for cosmetic appearance and static dissipation. The Goodrich kits are the same for both standard and Fastboot® neoprene de-icersEdge.

1/2 Pint ......P/N 06-03350 1 Quart ...... P/N 06-03351



### **CORROSION TECHNOLOGIES BOOT KLEAN**

Boot Klean removes debris old sealants quickly and easily from pneumatic deicing boots. Treat cleaned boots with CorrosionX Boot Sealant.

32 fl. oz. .....P/N 09-05646 5 Gallons......P/N 09-05646-5

# CORROSION TECHNOLOGIES

BOOT SEALANT
CorrosionX Boot Sealant is Step 2 in maintaining and properly protecting the surface of pneumatic de-icing boots. Boot Sealant prevents drying and cracking by sealing and protecting de-ice boots from harmful UV rays. Simply apply Boot Sealant to your de-icing boots with a soft cloth, and when dry, Boot Sealant stays slick and shiny for months! To prepare your de-ice boots for a treatment of Boot Sealant, it is important to first clean them and remove old, residual sealant by using CorrosionX Boot Klean .... P/N 09-05647



# **CORROSION TECHNOLOGIES**

Lav Chem Blue/Clear is a highly concentrated lavatory cleaner and deodorizer for aircraft and portable lavatories / toilets. Ideal for buses, trains and boats, Lav Chem Blue/Clear leaves a pleasant (i.e. not chemical) scent that keeps working long after similar products fail - leaving lavatories smelling and looking their best. Specifications:

• Use 2-3 ounces of Lav Chem Blue/Clear per gallon of water in storage tank.

 Use 1 ounce of Lav Chem Blue/Clear per 4 gallons of water for cleaning and deodorizing toilet areas.

Size	Color	Part No.	Price	Color	Part No.	Price
4 fl. oz.	Clear	09-05648		Blue	09-05649	
1 Gallon	Clear	09-05648-1		Blue	09-05649-1	
5 Gallon	Clear	09-05648-5		Blue	09-05649-5	



### **AVLAB DICE FLASH 190 FUEL** SYSTEM ICING INHIBITOR

Dice Flash 190 Fuel System Icing Inhibitor prevents undissolved water molecules from freezing in jet fuel, which would result in blockage of fuel lines and possibly engine failure. Meets U.S. Military specifications MIL-DTL-85470B and ASTM STANDARD D4171.

Pure DIETHYLENE GLYCOL MONOMETHYL ETHER, "carbitol". DICE Flash 190 is the identical chemical formulation utilized by the United States Air Force turbine fleet. This chemical replaces ethylene glycol monomethyl ether as a less toxic and non-hazardous fuel system icing inhibitor. Comparable to Prist.

20 Ounces.....P/N 05-21908 5 Gallons ......P/N 05-21909



### AVLAB TKS DE-ICING FLUID

TKS de-icing fluid complies with AL-5 DTD406B and is approved by British Aerospace. Aviation Laboratories aircraft wing de-icer is approved for all TKS systems. Diamond aircraft, HS-125 Hawker, Cirrus, Beechcraft, Cessna, Piper, Mooney, Kodiak, Hawker and many other air crafts are equipped with the TKS weeping wings de-icing systems. TKS wing

deicer is sold by the case, pail, and drum and accommodates all users from individual pilots and their aircraft to fleet managers and their growing fleets. TKS wing deicing fluid is tested before and after blending and undergoes strict quality control. Filtered to 1 micron. Certificate of analysis and strict lot control.

Size	Part No.	Price
1 Gallon	09-04827	
2.5 Gallon	09-04828	
5 Gallon	09-04829	
33 Gallon	09-04830	
55 Gallon	09-04831	