PS PRODUCT

LPS LOW SURFACE TENSION (LST)



A deep penetrating formulation attacks rust and corrosion to free "frozen" parts. LST has an extremely low surface tension that com-bines with a powerful foaming action to provide complete surface coverage, better penetration and improved moisture displacement.

LPS COPPER ANTI-SEIZE

Prevents seizure up to 1800°F (982°C). Lead free. Protects against seizure, heat-freeze, galling, rust and corrosion. Brushes easily. Highly adhesive on both wet and dry surfaces. Will not run, drip or settle out. Conforms to Mil-PRF-907E. Ideal for use on stainless steel and for joining dissimilar metals. Copper color 1/2 lb. can ... P/N 09-02908

LPS MAGNUM TEFLON LUBRICANT




LPS® Magnum Teflon® Lubricant provides ultra-high lubricity, plus the additive strength of Teflon® for high-temperature, highpressure environments. In even the most demanding situations, extend equipment life and reduce maintenance. 11 oz.Spray Can.....P/N 09-26430

LPS® HEAVY-DUTY SILICONE LUBRICANT



LPS FOOD GRADE SILICONE LUBRICANT



LPS® COLDGALVANIZE CORROSION INHIBITOR

• Zinc purity greater than 99% • Works like a hot-dip on ferrous metals indoors and outdoors • Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C) Commonly used as a flash rust preventive on welded areas . Long term protection • Flexible coating will not yellow, chalk, crack or peel • Electrochemically protects bare metal • Dries to touch in 3 to 5 minutes 14oz. (397g) – aerosol......P/N 09-26425

LPS KB-88 ULTIMATE PENETRANT



KB 88 has extremely high solvency and special additives to enhance penetration and attack corrosion. It makes the toughest maintenance job easier, faster, safer, and simpler. Formulated to attack and quickly release rusted and corroded nuts, bolts, hinges, and other frozen components. High KB solvency value of 151 and low surface tension and penetrates faster and deeper than most

other similar products in the market place. Displaces moisture with an aggressive formula that is NSF® Certified: H2 Registration # 138554 (Aerosol). This product is VOC compliant in all 50 states.

13 oz.....P/N 09-04027 20 oz.....P/N 09-04028

LPS NICKEL ANTI-SEIZE

• Contains no lead, copper or graphite • Prevents seizure up to 2600°F (1427°C) • Protects against rust and corrosion • For use in hostile environments and • extreme temperatures • Acid resistant • Strong resistance to water washoff • Brushable to -18°F (-27°C)

• Will not run, drip or settle out • Conforms to MIL-PRF-907E • Silver color. 1/2 LbP/N 09-04833 1 LbP/N 09-04834



LPS T-91 NON-SOLVENT DEGREASER

T-91 Non-Solvent Degreaser is biogradable, non-flammable, and has a neutral pH. T-91 is an excellent replacement for many solvent degreasers that have potential worker safety or flammability concerns. T-91 is ideal for solvent cleaning, part washers, and dip tanks and is more economical than most solvent degreasers in the marketplace. T-91 has an NSF® A1 registration (#141975) for use in food plants.

GallonP/N 09-02309 Case of 4 GallonsP/N 09-02309-4

LPS TRIFREE BRAKE CLEANER

The heavy-duty solvent for removal of brake fluid, grease, oil, and other contaminants.

Single......P/N 09-05843 Case of 12P/N 09-05843-12

LPS INSTANT SUPER DEGREASER 2.0

An industrial strength degreaser with no brominated solvents, trichlo-rethylene or perchloroethylene for an improved health and safety profile.

Case of 12 P/N 09-06057-12

LPS® TKX® ALL-PURPOSE LUBRICANT

All purpose, value lubricant which displaces moisture, loosens rusted or frozen parts and protects metal against corrosion. Safe to use on most surfaces. High flash point of 175°F (79°C). Inverta Spray Valve allows user to spray in an upright or inverted position. NSF® H2 registration. 11oz. (312g) – aerosol P/N 09-00148
HDX HEAVY-DUTY DEGREASER *

• Nonflammable • Removes oil, grease, wax, dirt, moisture, tar, • rake fluid and other contaminants • Fast evaporating • Low odor • Quick penetration • No residue • Non-conductive • NSF K1 registration # 059809: (aerosol); # 059810: (bulk) 19oz. (539g) – aerosolP/N 09-26407

LPS 1® PREMIUM LUBRICANT



Provides a dry, thin lubricating film. Resists oil, dust and dirt buildup. Fast acting penetration. Displaces moisture Loosens rusted or frozen parts. Provides a short term, light corrosion resistant barrier. Nonconductive Ideal for delicate mechanisms. Used worldwide in aviation. Safe on paint and most plastics.

11oz. (312g) – aerosolP/N 09-25900 1 gal. (3.78 l)P/N 09-26000

2® HEAVY-DUTY LUBRICANT



Strong, multi-purpose lubricant and penetrant with added corrosion protection. Provides a nondrying, light, oily film for use on indoor/outdoor equipment. Reduces wear caused by friction and corrosion. Displaces moisture Loosens rusted or frozen parts. Provides up to one year of protection. Nonconductive Safe on paint and most plastics. Inverta Spray Valve allows user to spray in an upright or inverted position. NSF® H2 registered.

11oz. (312g) – aerosolP/Ň 09-26100 20 oz. SprayP/N 09-04752 1 gal. (3.78 l)P/N 09-26200

LPS 3® PREMIER RUST INHIBITOR



years • Penetrates to displace moisture • Does not contain chlorinated solvents or silicone • Safe on most surfaces • Stops rust and corrosion • Provides non-sling lubrication • Provides anti-seize

coating • Inverta Spray Valve allows user to spray in an upright or inverted position • NSF® H2 registered #129027: (aerosol); #059849 (bulk) 11oz. (312g) – aerosolP/N 09-26300

20fl. oz. (591ml) – triggerP/N 09-01223 1 gal. (3.78 l)P/N 09-26400

LPS® QB PRECISION DUSTER

Patented formula - Patented US #6,342,471. Electrical contact cleaner. Cleans electrical parts without harming plastics. • Nonflammable • Plastic safe • Non-conductive • No residue • Replaces HCFC 141b contact cleaners • Fast evaporating • Conforms to CARB VOC requirements.

10 oz. spray can...... P/N 09-26210

LPS 2® BELT DRESSING



slippage and resist water wash out. Features: • May be used in wet, outdoor conditions • Does not deteriorate drive belts Eliminates squeaks from slipping belts • NSF® Certified: H1
Registration # 134508 8 Metal detectable plastic components-DETEXTM......P/N 09-04434

LPS CHAINMATE® CHAIN & WIRE ROPE LUBRICANT



ChainMate® Chain & Wire Rope Lubricant is moly-fortified and will perform under severe loads and extreme temperatures. Fortified with molybdenum disulfide, increases chain and wire rope life, effective under extreme pressure and temperature ranges. Contains water displacing solvents to quickly penetrate into cracks and core of wire rope.....P/N 09-04778

LPS A-151 SOLVENT DEGREASER

LPS A-151 Solvent Degreaser 15oz. Single......P/N 09-05423 Case of 12P/N 09-05423-12 STRONG STEEL STICKS

STRUNG STEEL STICK

Easy-to-use, hand-kneadable stick for immediate repairs to steel equipment and surfaces. Ideal for stopping leaks, even works on underwater applications. Permanently fills gaps and holes in metal, concrete, wood, fiberglass, and ceramics. Has a working time of 4 minutes, and will fully cure in 30 minutes to form a durable mass which can be machined, drilled, and painted. Can be used for many types of repairs, such as plumbing, electrical, ceramic, vehicle, equipment, and machinery. It is ideal for patching holes and cracks in pipes, drums, and tanks. 4 oz. stick.......P/N 09-26444

ATTENTION: Volatile Organic Compounds (VOCs) Government Regulations: Product cannot be purchased, sold or used in the states listed below. CA, CT, DC, DE, IL, IN, ME, MD, MA, MI, NH, NJ, NY, OH, PA, RI, VA

NOTE: FOR CASE OF 12 CANS OF LPS PRODUCTS ADD -12 TO THE PART NUMBER.